

CARTRIDGE TYPE CLEANING UNITS

CLEANCORE



CleanCore



Replacement Cartridge

The CleanCore cassette is supplied with a removable cartridge containing the cleaning fabric. The cartridge supports 400 cleaning cycles. Replacement cartridges can be purchased and installed into the CleanCore cassette, by the simple operation of unscrewing two retaining screws on the side of the unit. The cleaning fabric has a super fine cross woven weave, which permits dry cleaning of a fibre optic connector end face, through the simple action of two wipes down the length of exposed cleaning fabric.

APPLICATION

- Fiber network panels and assemblies
- Outdoor FTTH applications
- Cable assembly production facility
- Testing laboratories
- Servers, switches, routers and OADM with SC, FC, ST, MU and LC interface

FEATURES

- Designed for all types of simplex Connectors
- Compact size for easy hand-held operation
- Dry-clean without the use of harmful substances
- Replaceable cartridge (400 Cleaning Cycles)
- Constructed with anti-static Material

Specification

DRIVING METHOD	MANUALLY-PRESSED, FIXED-LENGTH FORWARDING	
Dimension (mm)	134mm L x 100mm W x 36mm	
Weight	< 85g	
Supported Connectors	2.5mm	FC, SC, ST, SMA,
	1.25mm	MU, LC, Biconic, DIN,
TYPE A (2 Slot) and TYPE B (Single Slot) Supported		

ORDER CODE CLEANCORE:

SCK-COR-100

ORDER CODE CARTRIDGE:

SCK-CAS-400

