

## CARTRIDGE TYPE CLEANING UNITS

### CLEANZONE



The revolutionary SENKO CLEANZONE has been specifically designed to offer the user a portable, automatic solution for cleaning the ferrule end face. With a compact, and ergonomic design, the SENKO CLEANZONE unit has a detachable, battery powered control unit and interchangeable, replaceable cartridges that allows single handed operation.

ORDER CODE COMPLETE SET LC MU

**SCK-CH-CC-125**

ORDER CODE COMPLETE SET SC-FC-ST:

**SCK-CH-CC-250**

## CLEANZONE

### ELECTRONIC CONTROL UNIT (ECU)



ORDER CODE

**SCK-CH**

## CLEANZONE

### LC - MU



ORDER CODE

**SCK-CC-125**

## CLEANZONE

### SC-FC-ST



ORDER CODE

**SCK-CC-250**

## FEATURES

- Patent Applied
- Automatic, electronically controlled, variable cleaning cycle 1-2 seconds (Trigger Operated).
- Dry clean solution for 1.25mm and 2.5mm in-situ connectors
- Field portable, high performance, rugged.
- 900 cleans per replaceable cartridge (1.25mm and 2.5mm variants).
- Built in Usage Indicator.
- Individual cartridges for 1.25mm and 2.5mm ferrule based connectors.
- Motor driven cleaning head.
- Operates off 2 x standard AA batteries.
- Extensive range of tip adaptors to support open market connector styles. FC, SC, ST, E-2000, LC, MU, LEMO. Design supports PC/UPC/APC ferrule types.
- Minimum cleaning zone 400 microns.
- Removes grease, dust, and other organic and inorganic contaminants
- Maximum weight 270 grams.
- Long reach nose (3 inches including tip adaptor) to ease access into ODF's
- Operating Temperature range -20°C to +40°C
- Storage Temperature range -30°C to +60°C

Each CLEANZONE cartridge is supplied with a 3 inch extension arm to improve access into densely packed adapter panels.